




Joint Reinforcement & Tanking Tape

Joint Reinforcement & Tanking
Tape for use with Tilemaster
Tanking Kit & Tanking Paste

TANKING KIT ACCESSORIES

-  Non-Adhesive Joint Tape For Use
With Tilemaster Tanking Paste
-  Suitable For Domestic & Commercial
Environments
-  Accessories Include Pre-Formed
Internal & External Corners

10 Mtr
ROLL

Non
Adhesive

Alkali
Resistant



TILEMASTER JOINT REINFORCEMENT & TANKING TAPE

DESCRIPTION:

Tilemaster Joint Reinforcement & Tanking Tape is an alkali resistant, dual layered woven mesh tape used for reinforcing internal and external joints and junctures in wet environments and forms part of the Tilemaster Tanking Waterproofing System when used with Tilemaster Tanking Kit & Tanking Paste.

Tilemaster Joint Reinforcement & Tanking Tape is a 10 metre roll length and is 100mm wide, allowing for sufficient bridging of hairline cracks on substrates and the reinforcement of internal and external corners before fully waterproofing the area.

PREPARATION:

Tilemaster Joint Reinforcement & Tanking Tape is to be used in conjunction with Tilemaster Tanking Kit & Tanking Paste. All instructions for preparation are included in the respective Technical Data Sheet (TDS) for Tilemaster Tanking Kit & Tanking Paste and should be referred to prior to installing Tilemaster Joint Reinforcement & Tanking Tape.

Adhesion Type	Non Adhesive
Roll Length	10 Mtrs
Roll Width	100mm
Application Temperature	5°C and rising
Storage	Store unopened in dry conditions
Colour	White
Note	All work must be carried out in accordance with British Standard Code of Practice for floor and wall tiling BS5385